

Kichler Lighting Outdoor fixtures are a reliable source of light, style and durability

Integrated LEDs deliver excellent light distribution and energy savings for 40,000 hours (to L70, or 70% initial lumens)

Durable materials and finishes, including our Climates™ collections, are quality tested to withstand the elements

Dark Sky certified options work to accommodate projects in which light pollution is a concern

Polycarbonate



A | 49802 BKTLED, PLLED

Polycarbonate



B | 49803 BKTLED, PLLED

White Glass



C | 49557 AZLED

White Glass



D | 49558 AZLED

Etched Glass



E | 49278 AZTLED, PLLED

Etched Glass



F | 49279 AZTLED, PLLED

	LED ITEM #	FINISH	LIGHT SOURCE	LED FIXTURE OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
A	49802	BKTLED, PLLED	(1) 25W	3000K, 90 CRI, 375 Lumens, 15 LPW	8.25W x 19H	4	9.5	Dimmable.
B	49803	BKTLED, PLLED	(1) 25W	3000K, 90 CRI, 475 Lumens, 19 LPW	9.5W x 24H	4	12	Dimmable.
C	49557	AZLED	(2) 40W	3000K, 90 CRI, 650 Lumens, 16 LPW	8W x 18.75H	4	10	Dimmable.
D	49558	AZLED	(2) 60W	3000K, 90 CRI, 875 Lumens, 15 LPW	8W x 25.25H	4	13.25	Dimmable.
E	49278	AZTLED, PLLED	(1) 8W	3000K, 90 CRI, 790 Lumens, 99 LPW	7W x 7.5H	4	3.75	Dimmable.
F	49279	AZTLED, PLLED	(2) 16W	3000K, 90 CRI, 1580 Lumens, 99 LPW	7W x 14H	4	7	Dimmable.

Measurements shown in inches. U.S. Patent Pending.