

Integrated LED – 120V-277V



	Small Accent – 5W		Small Accent – 10W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K - Pure White	4000K - Cool White	3000K - Pure White	4000K - Cool White
Item Number by Beam Spread and Finish	<b>15° Beam Spread</b> 16209 AZT30 16209 BKT30	<b>15° Beam Spread</b> 16209 AZT40 16209 BKT40	<b>15° Beam Spread</b> 16212 AZT30 16212 BKT30	<b>15° Beam Spread</b> 16212 AZT40* 16212 BKT40*
	<b>40° Beam Spread</b> 16210 AZT30 16210 BKT30	<b>40° Beam Spread</b> 16210 AZT40 16210 BKT40	<b>40° Beam Spread</b> 16213 AZT30 16213 BKT30	<b>40° Beam Spread</b> 16213 AZT40* 16213 BKT40*
	<b>55° Beam Spread</b> 16211 AZT30 16211 BKT30	<b>55° Beam Spread</b> 16211 AZT40 16211 BKT40	<b>55° Beam Spread</b> 16214 AZT30 16214 BKT30	<b>55° Beam Spread</b> 16214 AZT40* 16214 BKT40*
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	5W, .9pf 473-478 lm, 91-93 lm/W	5W, .9pf 495-514 lm, 93-100 lm/W	10W, .9pf 807-831 lm, 82-84 lm/W	10W, .9pf 914-942 lm, 91 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV.			
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 60,000 hrs.			
Notes	Replaces the equivalent of a 35W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed.		Replaces the equivalent of a 50W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed.	
Accessories	<b>15276</b> Power Post® <b>15601</b> Surface Mounting Flange <b>15609</b> Junction Box Mounting Bracket <b>15645, 15656, 15657, 15658</b> Stems		<b>16280</b> Long Visor/Cowl <b>16282</b> Hexcell Louver <b>16284</b> Frosted Lens <b>16286</b> Amber Lens <b>16288</b> Green Lens	
Dimensions				