



	Large Accent – 14W		Large Accent – 21W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K - Pure White	4000K - Cool White	3000K - Pure White	4000K - Cool White
Item Number by Beam Spread and Finish	15° Beam Spread 16215 AZT30* 16215 BKT30*	15° Beam Spread 16215 AZT40* 16215 BKT40*	15° Beam Spread 16218 AZT30* 16218 BKT30*	15° Beam Spread 16218 AZT40* 16218 BKT40*
	33° Beam Spread 16216 AZT30* 16216 BKT30*	33° Beam Spread 16216 AZT40* 16216 BKT40*	33° Beam Spread 16219 AZT30* 16219 BKT30*	33° Beam Spread 16219 AZT40* 16219 BKT40*
	55° Beam Spread 16217 AZT30* 16217 BKT30*	55° Beam Spread 16217 AZT40* 16217 BKT40*	55° Beam Spread 16220 AZT30* 16220 BKT30*	55° Beam Spread 16220 AZT40* 16220 BKT40*
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	14W, .9pf 1263-1326 lm 90-92 lm/W	14W, .9pf 1347-1424 lm 96-102 lm/W	21W, .9pf 1889-2033 lm 89-97 lm/W	21W, .9pf 1950-2111 lm 93-99 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV.			
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 60,000 hrs.			
Notes	Replaces the equivalent of a 90W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed.		Replaces the equivalent of a 35W Metal Halide. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal-proof hardware installed.	
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15645, 15656, 15657, 15658 Stems		16281 Long Visor/Cowl 16283 Hexcell Louver 16285 Frosted Lens 16287 Amber Lens 16289 Green Lens	
Dimensions				