

Integrated LED – 120V-277V



	Small Flood – 12W		Small Flood – 23W	
Finishes	AZT (shown), BKT		BKT (shown), AZT	
Color Temperature	3000K - Pure White	4000K - Cool White	3000K - Pure White	4000K - Cool White
Item Number by Mounting Type and Finish	Knuckle Mount: 16221 AZT30* 16221 BKT30*	Knuckle Mount: 16221 AZT40* 16221 BKT40*	Knuckle Mount: 16222 AZT30 16222 BKT30	Knuckle Mount: 16222 AZT40 16222 BKT40
	Trunnion Mount: 16221 AZT30TR* 16221 BKT30TR*	Trunnion Mount: 16221 AZT40TR* 16221 BKT40TR*	Trunnion Mount: 16222 AZT30TR 16222 BKT30TR	Trunnion Mount: 16222 AZT40TR 16222 BKT40TR
	Slip-Fit Mount: 16221 AZT30SL* 16221 BKT30SL*	Slip-Fit Mount: 16221 AZT40SL* 16221 BKT40SL*	Slip-Fit Mount: 16222 AZT30SL 16222 BKT30SL	Slip-Fit Mount: 16222 AZT40SL 16222 BKT40SL
Housing	Cast Aluminum		Cast Aluminum	
Wattage/pf, Delivered Lumens & Efficacy	12W, .9pf 1119 lm, 89 lm/W	12W, .9pf 1210 lm, 100 lm/W	23W, .9pf 2049 lm, 86 lm/W	23W, .9pf 2082 lm, 89 lm/W
CRI	80+		80+	
Voltage Range	120V-277V, 50-60Hz. Surge protection up to 4kV			
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 60,000 hrs.			
Notes	Replaces the equivalent of a 75W Halogen. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal proof hardware installed.		Replaces the equivalent of a 35W Metal Halide. Comes with 3 gel-filled wire nuts. IP66 rated. Vandal proof hardware installed.	
Accessories	15276 Power Post® 15601 Surface Mounting Flange 15609 Junction Box Mounting Bracket 15645, 15656, 15657, 15658 Stems			
Dimensions				