

Integrated LED – 12V



Small Accent with Variable Lumen Output

Finishes	AZT (shown), BKT, CBR, WHT (16016 only)		Additional Finishes
Color Temperature	2700K - Warm White	3000K - Pure White	<p>BKT</p> <p>CBR</p> <p>WHT (35° only)</p>
Item Number by Beam Spread and Finish	15° Spot 16015 AZT27, 16015 BKT27, 16015 CBR27 35° Flood 16016 AZT27, 16016 BKT27, 16016 CBR27, 16016 WHT27 60° Wide Flood 16017 AZT27, 16017 BKT27, 16017 CBR27	15° Spot 16015 AZT30, 16015 BKT30, 16015 CBR30 35° Flood 16016 AZT30, 16016 BKT30, 16016 CBR30, 16016 WHT30 60° Wide Flood 16017 AZT30, 16017 BKT30, 16017 CBR30	
Housing	Cast Aluminum or Cast Brass (CBR)		
Wattage/VA, Delivered Lumens & Efficacy	Level 1 = 2W/3.5VA, 100 lm, 50 lm/W Level 2 = 3.5W/5.5VA, 200 lm, 57 lm/W Level 3 = 5.5W/7.5VA, 300 lm, 55 lm/W	Factory set at Level 2 (200 lm/20W Equivalent) Lumen levels are the same for 2700K and 3000K	
CRI	80+	80+	
Voltage Range	9V-15V AC/DC with no loss in light output. 6kV (6000 volt surge protection) built on board of driver.		
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Custom reflector optics. Tested to a Lumen Maintenance L70 of 50,000 hrs.		
Wiring	48" of usable #18-2, SPT-1W leads		
Notes	Replaces the equivalent of a 10W Halogen (Level 1), 20W Halogen (Level 2) and 30-35W Halogen (Level 3). Includes 8" slotted in-ground stake, 2 gel-filled wire nuts and lumen switching magnetic key. Brass will naturally patina over time. White is only available in 35° Flood.		
Accessories	Cowls & Lenses: Long Cowl, 360 Degree Cowl, Hexcell Louver, Lenses: Red, Amber, Green Foliage, Holiday Green and Frosted	Mounting: Surface Mounting Flange, 3" Round Mounting Base (CBR), Surface Mounting Bracket, Junction Box Mounting Bracket, 90° Elbows, Stem Coupler, Stems, Two Fixture Mount (CBR)	<i>Accessories start on page 202.</i>

Dimensions

