

## Integrated LED – 12V



### LED Accent – 2.5W

Finishes	CBR (shown), AZT, BKT		Additional Finishes
Color Temperature	2700K - Warm White	3000K - Pure White	 AZT   BKT
Item Number by Beam Spread and Finish	<b>10° Spot</b> 16150 AZT27, 16150 BKT27, 16150 CBR27  <b>35° Flood</b> 16151 AZT27, 16151 BKT27, 16151 CBR27  <b>60° Wide Flood</b> 16152 AZT27, 16152 BKT27, 16152 CBR27	<b>10° Spot</b> 16150 AZT30, 16150 BKT30, 16150 CBR30  <b>35° Flood</b> 16151 AZT30, 16151 BKT30, 16151 CBR30  <b>60° Wide Flood</b> 16152 AZT30, 16152 BKT30, 16152 CBR30	
Housing	Cast Aluminum or Cast Brass (CBR)		
Wattage/VA, Delivered Lumens & Efficacy	2.5W, 3.5VA	200 lm, 80 lm/W	<i>Lumen levels are the same for 2700K and 3000K</i>
CRI	80+		
Voltage Range	9V-15V AC/DC with no loss in light output. 4kV (4000 volt surge protection).		
Light Source	3 integrated high-output LEDs with 3-step binning for color consistency. Custom T.I.R. (Total Internal Reflection) acrylic Lens. Tested to a Lumen Maintenance L70 of 40,000 hrs.		
Wiring	48" of usable #18-2, SPT-1W leads		
Notes	Replaces the equivalent of a 20W Halogen. Includes 8" slotted in-ground stake and 2 gel-filled wire nuts. Brass will naturally patina over time. Backed by a 10-year warranty - visit <a href="http://Kichler.com/Warranty">Kichler.com/Warranty</a> for details.		
Accessories	<b>Mounting:</b> 15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15609 Junction Box Mounting Bracket 15647, 15514 90° Elbow 15649 Stem Coupler 15645, 15656, 15657, 15658, 15570 Stems 15509, 15510, 15511, 15512, 15513 Stems (CBR) 15515 Two Fixture Mount (CBR)	15493 Round Mounting Base (CBR)  <b>Cowls &amp; Lenses:</b> 16076 Long Cowl 15875 AMB Amber Lens 15875 HGRN Holiday Green Lens 15875 RD Red Lens 15885 GRN Green Foliage Lens 15895 FRO Frosted Lens	
Dimensions			