



Integrated LED – 12V



## 2-in-1 Water Accent

Finishes	SS		
Color Temperature	2700K - Warm White	3000K - Pure White	4200K - Cool White
Item Number and Finish	15711 SS27	15711 SS	15711 SS42
Housing	Stainless Steel housing with integrated cowl		
Power Usage at 12V AC Input VA and Watts	3.4W, 4.9VA		
Color Temp. & CRI	2700K, 80+	3000K, 80+	4200K, 80+
Voltage Range	9V-15V AC/DC with no loss in light output		
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hours.		
Delivered Lumens & Efficacy	2700K = 135 lm 2700K = 40 lm/W	3000K = 150 lm 3000K = 44 lm/W	4200K = 180 lm 4200K = 53 lm/W
Wiring	25' of usable #18-2, SPT-2W leads		
Notes	Custom reflector optics. Filled and sealed with two types of premium encapsulant to ensure fixture is completely watertight, 1/4-20 threaded mounting tap. Can also be used out of water as a mini accent light. Not recommended for use in salt water.		



Name	Multi Fixture Weighted Base	Out of Water Bracket	Single Fixture Weighted Base
SKU & Finish	15776 BK	15777 SS	15778 BK
Notes	3.5W x 2.75H x 3.5L Unique heavy weighted 3-pronged underwater accessory for 2 or 3 fixtures (15711 sold separately) to give maximum flexibility and directional capability.	1.5W x 1.44H x 2.5L Stainless steel, easy-mount bracket (15711 sold separately) for use above ground on any surface – ideal for wood and masonry when used on decks, patios or overhangs.	3.5W x 2.75H x 3.5L Heavy weight 1-prong underwater light (15711 sold separately) accessory for standard installations. Provides advanced directional capability.