

Kichler® LED lighting exceeds the standards for efficiency, reliability and beauty

Long-life light emitting diodes (LED) provide approx. 40,000-hour life span to L70 (70% initial lumens) – about 5 years of standard operation

True optics: pure white light and controlled beam spread with no fade or drop off of light

High Color Rendering Index (CRI)

Standard installation



These devices comply with Part 15 of the FCC Regulations.

White Acrylic Diffuser



A | 10769 NILED
10769 OZLED

White Acrylic Diffuser



B | 10784 NILED
10784 OZLED

White Acrylic Diffuser



C | 10786 NILED
10786 OZLED

White Acrylic Diffuser



D | 10788 NILED
10788 OZLED

White Acrylic Diffuser



E | 10789 NILED
10789 OZLED

Acrylic Applied Tint w/ Painted Linen



F | 11302 CPLED
11302 NILED

| ITEM # | FINISH | LIGHT SOURCE | LED FIXTURE OUTPUT | DIMENSIONS | EXT. | HCWO | NOTES |
|--------|--------------------|--------------|------------------------------------|---------------------|------|------|--|
| A | 10769 NILED, OZLED | (1) 28.5W | 3000K, 90 CRI, 1900 Lumens, 66 LPW | 14W x 3.75H | 4 | 7 | Dimmable. Ceiling or wall mount. |
| B | 10784 NILED, OZLED | (1) 23W | 3000K, 90 CRI, 1280 Lumens, 56 LPW | 11.75W x 3.5H | 3.5 | 6 | Dimmable. Ceiling or wall mount. |
| C | 10786 NILED, OZLED | (1) 34W | 3000K, 90 CRI, 1790 Lumens, 53 LPW | 17.75W x 4.25H | 4.25 | 8.75 | Dimmable. Ceiling or wall mount. |
| D | 10788 NILED, OZLED | (1) 48W | 3000K, 90 CRI, 3725 Lumens, 78 LPW | 24W x 4.75H | 4.75 | 12 | Dimmable. Ceiling or wall mount. |
| E | 10789 NILED, OZLED | (1) 54W | 3000K, 90 CRI, 3750 Lumens, 69 LPW | 32.5L x 18W x 4.75H | 4.75 | 9 | Dimmable. Oval Shape. Ceiling or wall mount. |
| F | 11302 CPLED, NILED | (1) 18.5W | 3000K, 90 CRI, 1150 Lumens, 62 LPW | 12W x 3.75H | --- | --- | Dimmable. |

Measurements shown in inches. Delivered Lumens shown.