



The breadth of Kichler Lighting Products for Professional Lighting Solutions has expanded to feature more:

Universal Voltage (120V-277V) on select Sconce and Vanity fixtures

Energy Star® and Title 24 qualified fixtures to ensure quality light output and efficiency

Durable components that have been tested and re-tested to withstand 24/7 illumination

White Acrylic Diffuser



J | 11315 NILED, OZLED

White Acrylic Diffuser




K | 11319 NILED, OZLED

White Acrylic Diffuser with Natural Linen



L | 10421 SNLED

White Acrylic Diffuser with White Linen



M | 10438 NCHLED

White Acrylic Diffuser with White Linen



N | 10439 NCHLED

White Acrylic Diffuser



O | 10620 NILED

	ITEM #	FINISH	LIGHT SOURCE	LED FIXTURE OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
J	11315	NILED, OZLED	(1) 22W	3000K, 90 CRI, 1375 Lumens, 63 LPW	7W x 16H	3.75	8	Dimmable. 120-277V
K	11319	NILED, OZLED	(1) 15W	3000K, 90 CRI, 925 Lumens, 62 LPW	9.5W x 10.75H	3.75	5.25	Dimmable. 120-277V
L	10421	SNLED	(1) 16W	3000K, 90 CRI, 910 Lumens, 57 LPW	12W x 10H	4	5	Dimmable. Linen shade.
M	10438	NCHLED	(1) 8W	3000K, 90 CRI, 420 Lumens, 53 LPW	5.5W x 14.25H	3.75	5.25	Dimmable. Linen shade.
N	10439	NCHLED	(1) 16W	3000K, 90 CRI, 880 Lumens, 55 LPW	11W x 14.25H	3.75	5.25	Dimmable. Linen shade.
O	10620	NILED	(1) 16W	3000K, 90 CRI, 790 Lumens, 50 LPW	13W x 9.5H	4	5	Dimmable.

Measurements shown in inches.