



LED Options

Satin Etched Cased Opal Glass



E | 5096 NI, OZS
5096 NIL18, OZSL18

Satin Etched Cased Opal Glass



F | 45921 NI, OZ
45921 NIL18, OZL18

Satin Etched White Glass



G | 5388 NI, OZ
5388 NIL18, OZL18

Satin Etched Cased Opal Glass



H | 45568 NI, OZ
45568 NIL18, OZL18

Satin Etched White Glass



I | 45504 NI, OZ
45504 NIL18, OZL18

Satin Etched Glass



J | 45637 CH, NI, OZ
45637 CHL18, NIL18, OZL18

NI: Satin Etched Glass
OZ: Light Umber Etched Glass



K | 43170 NI, OZ
43170 NIL18, OZL18

Satin Etched Glass



L | 45938 NI, OZ
45938 NIL18, OZL18

Satin Etched Glass



M | 45901 NI, OZ
45901 NIL18, OZL18

ITEM #	FINISH	LIGHT SOURCE	LED BULB OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
E	NI, OZS	(1) 100W (M)	---	4.5W x 10.75H	7	5.75	Ⓧ May be installed with glass up or down.
E	NIL18, OZSL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	4.5W x 10.75H	7	5.75	Ⓧ Dimmable. May be installed with glass up or down.
F	NI, OZ	(1) 100W (M)	---	5W x 18.25H	5.25	9	Ⓧ May be installed with glass up or down.
F	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	5W x 18.25H	5.25	9	Ⓧ Dimmable. May be installed with glass up or down.
G	NI, OZ	(1) 100W (M)	---	7.25W x 7.75H	8.25	4.5	Ⓧ May be installed with glass up or down.
G	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	7.25W x 7.75H	8.25	4.5	Ⓧ Dimmable. May be installed with glass up or down.
H	NI, OZ	(1) 100W (M)	---	5.5W x 10.75H	7.25	5.5	Ⓧ May be installed with glass up or down.
H	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	5.5W x 10.75H	7.25	5.5	Ⓧ Dimmable. May be installed with glass up or down.
I	NI, OZ	(1) 100W (M)	---	5.75W x 8.5H	9.25	3.25	Ⓧ May be installed with glass up or down.
I	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	5.75W x 8.5H	9.25	3.25	Ⓧ Dimmable. May be installed with glass up or down.
J	CH, NI, OZ	(1) 100W (M)	---	5W x 9H	6.25	4.25	Ⓧ May be installed with glass up or down.
J	CHL18, NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	5W x 9H	6.25	4.25	Ⓧ Dimmable. May be installed with glass up or down.
K	NI, OZ	(1) 100W (M)	---	6W x 14H	9.25	8	Ⓧ May be installed with glass up or down.
K	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	6W x 14H	9.25	8	Ⓧ Dimmable. May be installed with glass up or down.
L	NI, OZ	(1) 100W (M)	---	6.5W x 10.75H	8.75	5	Ⓧ May be installed with glass up or down.
L	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	6.5W x 10.75H	8.75	5	Ⓧ Dimmable. May be installed with glass up or down.
M	NI, OZ	(1) 100W (M)	---	6W x 9.25H	8.5	5.25	Ⓧ May be installed with glass up or down.
M	NIL18, OZL18	(1) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	6W x 9.25H	8.5	5.25	Ⓧ Dimmable. May be installed with glass up or down.

Measurements shown in inches.