



ITEM #	FINISH	LIGHT SOURCE	LED FIXTURE OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
H	45657	CHLED	(2) 23W 3000K, 90 CRI, 1551 Lumens, 66 LPW	22W x 4.5H	3.5	2.25	Dimmable. May be installed vertically or horizontally.
I	45658	CHLED	(3) 38.5W 3000K, 90 CRI, 2499 Lumens, 64 LPW	32W x 4.5H	3.5	2.25	Dimmable. May be installed vertically or horizontally.
J	45801	CHLED	(1) 20W 3000K, 90 CRI, 900 Lumens, 45 LPW	18.25W x 5.5H	3.5	2.75	Dimmable. May be installed vertically or horizontally.
K	45838	CHLED, OZLED	(1) 25W 3000K, 90 CRI, 1200 Lumens, 46 LPW	24.25W x 5.5H	3.5	2.75	Dimmable. May be installed vertically or horizontally.
L	45839	CHLED, OZLED	(1) 30W 3000K, 90 CRI, 1275 Lumens, 43 LPW	30.25W x 5.5H	3.5	2.75	Dimmable. May be installed vertically or horizontally.
M	10798	NILED	(2) 32W 3000K, 90 CRI, 1740 Lumens, 54 LPW	19.25W x 6H	3.5	3	Dimmable.
N	10799	NILED	(3) 48W 3000K, 90 CRI, 2640 Lumens, 54 LPW	30W x 6H	3.5	3	Dimmable.
O	10800	NILED	(4) 64W 3000K, 90 CRI, 3540 Lumens, 55 LPW	40.75W x 6H	3.5	3	Dimmable.

Measurements shown in inches.