

Satin Etched White Glass



A | 45685 NBRLED, PNLED

Satin Etched White Glass



B | 45682 CHLED

Satin Etched White Glass



C | 45683 CHLED

Satin Etched White Glass



D | 45679 CHLED, NILED

Satin Etched White Glass



E | 45680 CHLED, NILED

White Polycarbonate



F | 11141 NILED

White Polycarbonate



G | 11142 NILED

White Polycarbonate



H | 11143 NILED

White Polycarbonate



I | 11144 NILED

ITEM #	FINISH	LIGHT SOURCE	LED FIXTURE OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
A	45685 NBRLED, PNLED	(2) 31W	3000K, 90 CRI, 1915 Lumens, 61 LPW	27W x 5H	3.75	2.5	Dimmable. May be installed vertically or horizontally.
B	45682 CHLED	(2) 31W	3000K, 90 CRI, 1650 Lumens, 53 LPW	24.75W x 5H	3.25	2.5	Dimmable. May be installed vertically or horizontally.
C	45683 CHLED	(4) 46W	3000K, 90 CRI, 2470 Lumens, 53 LPW	36.5W x 5H	3.25	2.5	Dimmable. May be installed vertically or horizontally.
D	45679 CHLED, NILED	(2) 31W	3000K, 90 CRI, 1650 Lumens, 53 LPW	26.5W x 5H	3.5	2.5	Dimmable. May be installed vertically or horizontally.
E	45680 CHLED, NILED	(4) 46W	3000K, 90 CRI, 2470 Lumens, 53 LPW	38.5W x 5H	3.5	2.5	Dimmable. May be installed vertically or horizontally.
F	11141 NILED	(1) 10W	3000K, 90 CRI, 640 Lumens, 64 LPW	12.75W x 4.5H	4	2.25	Dimmable. May be installed vertically or horizontally.
G	11142 NILED	(1) 20W	3000K, 90 CRI, 1410 Lumens, 71 LPW	24.75W x 4.5H	4	2.25	Dimmable. May be installed vertically or horizontally.
H	11143 NILED	(1) 25.5W	3000K, 90 CRI, 1960 Lumens, 77 LPW	36.5W x 4.5H	4	2.25	Dimmable. May be installed vertically or horizontally.
I	11144 NILED	(1) 38W	3000K, 90 CRI, 3030 Lumens, 80 LPW	48.75W x 4.5H	4	2.25	Dimmable. May be installed vertically or horizontally.

Measurements shown in inches.

= ADA Compliant = DAMP = WET = Dark Sky Compliant = LED Integrated = Lamp Included = CFL Lamp Included = LED Bulb Included