



ITEM #	FINISH	LIGHT SOURCE	LED FIXTURE OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
J	11253	NILED (1) 22W	3000K, 90 CRI, 1425 Lumens, 70 LPW	24.75W x 4.75H	3.75	2.5	Dimmable. May be installed vertically or horizontally. 120V-277V.
K	11254	NILED (1) 25W	3000K, 90 CRI, 1725 Lumens, 69 LPW	36.75W x 4.75H	3.75	2.5	Dimmable. May be installed vertically or horizontally. 120V-277V.
L	11255	NILED (1) 38W	3000K, 90 CRI, 2525 Lumens, 72 LPW	48.5W x 4.75H	3.75	2.5	Dimmable. May be installed vertically or horizontally. 120V-277V.
M	11146	NILED (1) 19W	3000K, 90 CRI, 1420 Lumens, 75 LPW	25.75W x 4.75H	4.25	2.25	Dimmable. May be installed vertically or horizontally. 120V-277V.
N	11147	NILED (1) 23W	3000K, 90 CRI, 1850 Lumens, 75 LPW	37.5W x 4.75H	4.25	2.25	Dimmable. May be installed vertically or horizontally. 120V-277V.
O	11148	NILED (1) 38W	3000K, 90 CRI, 2680 Lumens, 71 LPW	49.25W x 4.75H	4.25	4.25	Dimmable. May be installed vertically or horizontally. 120V-277V.
P	11149	NILED (1) 19W	3000K, 90 CRI, 1440 Lumens, 76 LPW	25.5W x 4.75H	4	2.25	Dimmable. May be installed vertically or horizontally. 120V-277V.
Q	11150	NILED (1) 23W	3000K, 90 CRI, 1890 Lumens, 82 LPW	37.25W x 4.75H	4	2.25	Dimmable. May be installed vertically or horizontally. 120V-277V.
R	11151	NILED (1) 38W	3000K, 90 CRI, 2750 Lumens, 72 LPW	49W x 4.75H	4	2.25	Dimmable. May be installed vertically or horizontally. 120V-277V.

Measurements shown in inches.