


Indoor Lighting

Vanity – LED Options

Satin Etched Cased Opal Glass



A 45922 NI, OZ
45922 NIL18, OZL18

Satin Etched Cased Opal Glass



B 45923 NI, OZ
45923 NIL18, OZL18

Satin Etched Cased Opal Glass



C 45924 NI, OZ
45924 NIL18, OZL18

Satin Etched Glass



D 45638 CH, NI, OZ
45638 CHL18, NIL18, OZL18

Satin Etched Glass



E 45639 CH, NI, OZ
45639 CHL18, NIL18, OZL18

Satin Etched Glass



F 45640 CH, NI, OZ
45640 CHL18, NIL18, OZL18

NI: Satin Etched Glass
OZ: Light Umber Etched Glass



G 45054 NI, OZ
45054 NIL18, OZL18

NI: Satin Etched Glass
OZ: Light Umber Etched Glass



H 45055 NI, OZ
45055 NIL18, OZL18

NI: Satin Etched Glass
OZ: Light Umber Etched Glass



I 45056 NI, OZ
45056 NIL18, OZL18

ITEM #	FINISH	LIGHT SOURCE	LED BULB OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
A	45922 NI, OZ	(2) 100W (M)	---	14W x 9.25H	5.25	6.75	Ⓚ May be installed with glass up or down.
A	45922 NIL18, OZL18	(2) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	14W x 9.25H	5.25	6.75	Ⓚ Dimmable. May be installed with glass up or down.
B	45923 NI, OZ	(3) 100W (M)	---	24W x 9.25H	5.25	6.75	Ⓚ May be installed with glass up or down.
B	45923 NIL18, OZL18	(3) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	24W x 9.25H	5.25	6.75	Ⓚ Dimmable. May be installed with glass up or down.
C	45924 NI, OZ	(4) 100W (M)	---	34W x 9.25H	5.25	6.75	Ⓚ May be installed with glass up or down.
C	45924 NIL18, OZL18	(4) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	34W x 9.25H	5.25	6.75	Ⓚ Dimmable. May be installed with glass up or down.
D	45638 CH, NI, OZ	(2) 100W (M)	---	13W x 9.25H	8	4.75	Ⓚ May be installed with glass up or down.
D	45638 CHL18, NIL18, OZL18	(2) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	13W x 9.25H	8	4.75	Ⓚ Dimmable. May be installed with glass up or down.
E	45639 CH, NI, OZ	(3) 100W (M)	---	20.25W x 9.25H	8	4.75	Ⓚ May be installed with glass up or down.
E	45639 CHL18, NIL18, OZL18	(3) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	20.25W x 9.25H	8	4.75	Ⓚ Dimmable. May be installed with glass up or down.
F	45640 CH, NI, OZ	(4) 100W (M)	---	28W x 9.25H	8	4.75	Ⓚ May be installed with glass up or down.
F	45640 CHL18, NIL18, OZL18	(4) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	28W x 9.25H	8	4.75	Ⓚ Dimmable. May be installed with glass up or down.
G	45054 NI, OZ	(2) 100W (M)	---	18W x 11.5H	8	6.5	Ⓚ May be installed with glass up or down.
G	45054 NIL18, OZL18	(2) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	18W x 11.5H	8	6.5	Ⓚ Dimmable. May be installed with glass up or down.
H	45055 NI, OZ	(3) 100W (M)	---	24W x 11.5H	8	6.5	Ⓚ May be installed with glass up or down.
H	45055 NIL18, OZL18	(3) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	24W x 11.5H	8	6.5	Ⓚ Dimmable. May be installed with glass up or down.
I	45056 NI, OZ	(4) 100W (M)	---	36W x 11.5H	8	6.5	Ⓚ May be installed with glass up or down.
I	45056 NIL18, OZL18	(4) 10W (M)	3000K, 92 CRI, 800 Lumens, 80 LPW	36W x 11.5H	8	6.5	Ⓚ Dimmable. May be installed with glass up or down.

Measurements shown in inches.

= ADA Compliant = DAMP = WET = Dark Sky Compliant = LED Integrated = Lamp Included = CFL Lamp Included = LED Bulb Included