

## Quality and value lighting for any application.

A low-profile design, durable finish and gently diffused light output make these LED fixtures a true value—ideal for a variety of applications, from single-family homes to multi-unit structures.



Shown: 4U27K12WHT

|                    |  | Finish, Color Temperature and Size   |                    |   |                    |                        |  |
|--------------------|--|--|--------------------|---|--------------------|------------------------|--|
| Available Finishes | Textured Bronze (BZT), Textured White (WHT)  |  |                    |   | Available Finishes |                        |  |
| Color Temperature  | 2700K - Warm White   |  | 3000K - Pure White |   |                    |                        |  |
| Size               | 8"   | <b>4U27K08</b> BZT, WHT<br>8" L x 4.5" W x 1.1" H<br>175 delivered lumens<br>4 Watts   | 8"                 | <b>4U30K08</b> BZT, WHT<br>8" L x 4.5" W x 1.1" H<br>200 delivered lumens<br>4 Watts  |                    | BZT<br><br><br><br>WHT |  |
|                    | 12"  | <b>4U27K12</b> BZT, WHT<br>12" L x 4.5" W x 1.1" H<br>250 delivered lumens<br>6 Watts  | 12"                | <b>4U30K12</b> BZT, WHT<br>12" L x 4.5" W x 1.1" H<br>285 delivered lumens<br>6 Watts   |                    |                        |  |
|                    | 22"  | <b>4U27K22</b> BZT, WHT<br>22" L x 4.5" W x 1.1" H<br>485 delivered lumens<br>10 Watts | 22"                | <b>4U30K22</b> BZT, WHT<br>22" L x 4.5" W x 1.1" H<br>560 delivered lumens<br>10 Watts  |                    |                        |  |
|                    | 30"  | <b>4U27K30</b> BZT, WHT<br>30" L x 4.5" W x 1.1" H<br>650 delivered lumens<br>14 Watts | 30"                | <b>4U30K30</b> BZT, WHT<br>30" L x 4.5" W x 1.1" H<br>750 delivered lumens<br>14 Watts  |                    |                        |  |
| Benefits           | <b>Product Benefits</b> <ul style="list-style-type: none"> <li>• Quality, diffused light output</li> <li>• 90 CRI keeps furnishings true-to-color</li> <li>• Replaceable driver extends the life of the fixture</li> <li>• Energy efficient, LED light source</li> <li>• FCC compliant and can be used to comply with 2016 Title 24, Part 6 High efficacy LED light source requirements</li> <li>• Durable powder coat finish</li> <li>• Dimmable with standard wall dimmer</li> </ul> |  |                    | <b>Installation Benefits</b> <ul style="list-style-type: none"> <li>• Captive screws for quick installation</li> <li>• Direct wire and linkable</li> <li>• Knockouts in sides and in back of fixture</li> <li>• 1" profile, 4.5" depth</li> <li>• BX connector 10589 included with fixture</li> </ul> |                    |                        |  |
| Warranty           | 3-year residential warranty. 1-year commercial warranty. See <a href="http://Kichler.com/warranty">Kichler.com/warranty</a> for complete details.  |  |                    |   |                    |                        |  |
| Accessories        | See page 88 for available cables, connectors and cords. For recommended dimmers visit <a href="http://Kichler.com/dimming">Kichler.com/dimming</a> .   |  |                    |   |                    |                        |  |



JAB-2016