A low voltage design and the ability to cut to 2" increments makes the 4T Series ideal for short runs and smaller spaces, like lining shelves or cabinets.



Shown: 4T1100H30WH

		Finish, Color Temperature, Lumens and Size					
Location Use	Dry Locations Only White (WH)						
Available Finish							
Color Temperature	2700K - Warm White		3000K - Pure White		5000K - Bright White		
Standard Output • 16' max. linear run length • 120–140 delivered lumens per foot • 1.5W per foot, 90 CRI • Cuttable every 2"	16'	4T116S27 WH 24 Watts	16'	4T116S30 WH 24 Watts	16'	4T116S50 WH 24 Watts	
	100'	4T1100S27 WH	100'	4T1100S30 WH	100'	4T1100S50 WH	
High Output • 16' max. linear run length • 210–260 delivered lumens per foot • 3W per foot, 90 CRI • Cuttable every 2"	16'	4T116H27 WH 48 Watts	16'	4T116H30 WH 48 Watts	16'	4T116H50 WH 48 Watts	
	100'	4T1100H27 WH	100'	4T1100H30 WH	100'	4T1100H50 WH	
Supply Wire	Tape light rolls come with a 2' supply wire soldered to the beginning and end of each roll.						
Warranty	3-year residential warranty. 1-year commercial warranty. See Kichler.com/warranty for complete details.						
Additional Info	For recommended dimmers visit Kichler.com/dimming.						

Build your lighting system

The ability to build a lighting system is one of the many things that makes low-voltage LED tape and accent lighting so versatile. With the right components, you can install lighting just about anywhere your supply wire can take you, including coves, toe kicks, shelving or drawers. To build your system, you'll need:



