

120V-277V LED Lamps

| LAMP | BASE / LAMP TYPE | WATTS | KELVIN / LUMENS | BEAM ANGLE/ITEM # | |
|---|--|-----------------------------------|------------------------------|-------------------|------------------|
| | | | | 25° Spot | 40° Flood |
|  | PAR20 Wet Location W | 7W Compares up to 35W Halogen | 2700K – Warm White 310 lm | 18081 | 18084 |
| | | | 3000K – Pure White 330 lm | 18082 | 18085 |
| | | | 4200K – Cool White 350 lm | 18083 | 18086 |
| | | | | 25° Spot | 40° Flood |
|  | PAR30 Wet Location W | 12W Compares up to 50W Halogen | 2700K – Warm White 580Lm | 18087 | 18090 |
| | | | 3000K – Pure White 610Lm | 18088 | 18091 |
| | | | 4200K – Cool White 640Lm | 18089 | 18092 |
| | | | | 25° Spot | 40° Flood |
|  | PAR30 Longneck Wet Location W | 12W Compares up to 50W Halogen | 2700K – Warm White 580Lm | 18111 | 18114 |
| | | | 3000K – Pure White 610Lm | 18112 | 18115 |
| | | | 4200K – Cool White 640Lm | 18113 | 18116 |
| | | | | 25° Spot | 40° Flood |
|  | PAR38 Wet Location W | 17W Compares up to 75W Halogen | 2700K – Warm White 800Lm | 18093 | 18096 |
| | | | 3000K – Pure White 850Lm | 18094 | 18097 |
| | | | 4200K – Cool White 900Lm | 18095 | 18098 |

W Wet location versions designed and listed for use in an enclosed or open fixture. Using lamp in enclosed fixtures can result in up to 30-40% loss in lumen output based on test data.