# INCLUDED FEATURES

Blades (5) Included

- Variable Pitch
- 15" Sweep
- Non-reversible
- Polycarbonate

**Downrods** 4.5" Downrod with 1" (O.D.)

**Downlight** Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 3,000K

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

**Control** CoolTouch<sup>™</sup> Control System - Full Function

### FAN FEATURES

Mounting Slope - Pitch Flat ceiling only

Lead Wire 78"

cUL Listed Damp

Hanging Weight 15.9 lbs.

**Body Material** Steel

Warranty www.Kichler.com/Warranty

# MOTOR FEATURES

Motor Size/Type 153mm X 15mm, AC

Amps 0.28 on High

**RPM** 322 on High

Energy Star® No

# INCLUDED CONTROLS



## COOLTOUCH™ CONTROL SYSTEM -FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Manual Reverse
- Lights On/Off with Full-Range Dimming

#### OPTIONAL CONTROLS



WALL TRANSMITTER -FULL FUNCTION 370038 (Shown)

# **BLADE SPECS**

Blade Finish & Part Number (Side 1) (Reversible)

Fan Finish










# HANGING MEASUREMENTS

#### WITH 4.5" DOWNROD


Fixture Drop (from ceiling)	Blade Drop (from ceiling)	<b>Housing</b> (width)	Ceiling Canopy (width)
<b>A:</b> 20.00"	<b>B:</b> 19.25"	<b>C:</b> 10.50"	<b>D:</b> 6.25"



AIR PERFORMANCE			
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt	
351	33	11	







Terna<sup>™</sup>'s contoured blade design produces a unique outward airflow pattern to cool a wider area.