

INCLUDED FEATURES

- Blades (2) Included**
 - 28° Pitch
 - 54" Sweep
 - Non-reversible
 - ABS
- Downrods N/A**
- Downlight N/A**
- Downlight Glass N/A**
- Optional Downlight N/A**
- Uplight N/A**
- Uplight Glass N/A**
- Low Ceiling Adaptable No**
- Control 6-Speed DC CoolTouch™ Control System**

FAN FEATURES

- Mounting Slope – Pitch Flat ceiling only**
- Lead Wire 8"**
- cETL Listed Indoor**
- Hanging Weight 18.7 lbs.**
- Body Material Steel**
- Warranty www.Kichler.com/Warranty**

MOTOR FEATURES

- Motor Size/Type DC-125**
- Amps 0.54 on High**
- RPM 132 on High**
- Energy Star® No**

INCLUDED CONTROLS



- 6-SPEED DC COOLTOUCH™ CONTROL SYSTEM**
- 6 Forward Speeds, Reverse & Motor Off
 - Lights On/Off with Full-Range Dimming
 - No More Than Two Fans on One Circuit

OPTIONAL CONTROLS




- 6-SPEED DC WALL TRANSMITTER 370036 (Shown)**

BLADE SPECS

Blade Finish & Part Number (Side 1)	Fan Finish (Reversible)
Silver FB300168 NI	NI Brushed Nickel
Dark Oak FB300168 OBB	OBB Oil Brushed Bronze™
Walnut FB300168 PN	PN Polished Nickel

HANGING MEASUREMENTS

FLUSH MOUNT			
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 24.25"	B: 24.25"	C: 8.00"	D: 8.00"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5780	31	184

