# INCLUDED FEATURES

Blades (7) Included

- 12° Pitch
- 80" Sweep
- Non-reversible
- ABS

Downrods 8" Downrod with 1" (O.D.)

Downlight N/A

Downlight Glass N/A

Optional Downlight See pages 318-320

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

**Control** 6-Speed DC CoolTouch™ Control System

# FAN FEATURES

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78"

**cUL Listed** Wet

Hanging Weight 30.8 lbs.

**Body Material ABS** 

Warranty www.Kichler.com/Warranty

### MOTOR FEATURES

Motor Size/Type DC-165L

Amps 0.56 on High

RPM 78 on High

Energy Star® No

# INCLUDED CONTROLS



## 6-SPEED DC COOLTOUCH™ CONTROL SYSTEM

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- No More Than Two Fans on One Circuit

#### OPTIONAL CONTROLS



6-SPEED DC WALL TRANSMITTER -FULL FUNCTION 370036 (Shown)

# COORDINATING LIGHTING

To see the complete LED Outdoor Wall Collection visit Kichler.com.



Outdoor Wall Sconce 11309BKTLED

## **BLADE SPECS**

Blade Finish & Part Number (Side 1) (Reversible)

Fan Finish

Antique Satin Silver FB310115 ANS












# HANGING MEASUREMENTS

## WITH 8" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
<b>A:</b> 15.50"	<b>B:</b> 13.50"	<b>C:</b> 10.25"	<b>D:</b> 6.75"




AIR PERFORMANCE				
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt		
7744	33	237		









CLIMATES<sup>™</sup>-grade fans are built with impressive corrosion-resistant materials to withstand harsh outdoor elements: extreme heat, saltwater spray, intense cold and constant UV exposure.