

INCLUDED FEATURES

Blades (3) Included

- 17° Pitch
- 44" Sweep
- Non-reversible
- ABS

Downrods Optional 337033 Downrod Kit

Downlight Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 80 CRI, 3,000K

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Flush Mount

Control Wall Transmitter - Full Function

FAN FEATURES

Mounting Slope – Pitch Flat ceiling only

Lead Wire 78"

cETL Listed Wet

Hanging Weight 15.7 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 172mmX 15mm, AC

Amps 0.57 on High

RPM 170 on High

Energy Star® No

INCLUDED CONTROLS



WALL TRANSMITTER - FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Manual Reverse
- Lights On/Off with Full-Range Dimming

OPTIONAL CONTROLS



COOLTOUCH™ TRANSMITTER - FULL FUNCTION

337009 (Shown)

METAL CAPS

Includes a metal fixture cap for non-light use.



OPTIONAL HANGER SYSTEM



Downrod Kit
337033 MWH, NI (shown), OZ

BLADE SPECS


Blade Finish & Part Number (Side 1) **Fan Finish (Reversible)**

Matte White FB330151 MWH	MWH Matte White
Silver FB330151 NI	NI Brushed Nickel
Brown FB330151 OZ	OZ Olde Bronze®

HANGING MEASUREMENTS

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 11.00"	B: 7.25"	C: 8.75"	D: 6.50"



OPTIONAL HANGER SYSTEM

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 15.00"	B: 11.25"	C: 8.75"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4298	68	63

AIR PERFORMANCE (OPT.)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4705	68	77