

INCLUDED FEATURES

Blades (3) Included

- 22° Pitch
- 34" Sweep
- Non-reversible
- ABS

Downrods Optional 337033 Downrod Kit

Downlight Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 80 CRI, 3,000K

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Flush Mount

Control Wall Transmitter - Full Function

FAN FEATURES

Mounting Slope – Pitch Flat ceiling only

Lead Wire 78"

cETL Listed Wet

Hanging Weight 14.6 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 172mm X 12mm, AC

Amps 0.54 on High

RPM 226 on High

Energy Star® No

INCLUDED CONTROLS



WALL TRANSMITTER - FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Manual Reverse
- Lights On/Off with Full-Range Dimming

OPTIONAL CONTROLS



COOLTOUCH™ TRANSMITTER - FULL FUNCTION

337009 (Shown)

METAL CAPS

Includes a metal fixture cap for non-light use.



OPTIONAL HANGER SYSTEM



Downrod Kit
337033 MWH (shown), NI, OZ

BLADE SPECS

Blade Finish & Part Number (Side 1) Fan Finish (Reversible)



Matte White
FB330150
MWH



MWH
Matte White



Silver
FB330150
NI



NI
Brushed Nickel



Brown
FB330150
OZ




OZ
Olde Bronze®

HANGING MEASUREMENTS

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 11.00"	B: 7.25"	C: 8.75"	D: 6.50"



OPTIONAL HANGER SYSTEM

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 15.00"	B: 11.25"	C: 8.75"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
3509	65	54

AIR PERFORMANCE (OPT.)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
3831	65	65