

INCLUDED FEATURES

Blades (5) Included

- 14° Pitch
- 44" Sweep
- Reversible
- ABS

Downrods 12" Downrod with 1" (O.D.)

Downlight Replaceable. Includes (4) E12, 40W Krypton/T3 Lamps, 5907FST

Downlight Glass Fresnel Lens

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Flush Mount Canopy included. *Note: Décor trim must be removed for Flush Mount.*

Control CoolTouch™ Transmitter - Full Function

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 24.5 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 153mm X 17mm, AC

Amps 0.45 on High

RPM 217 on High

Energy Star® No

INCLUDED CONTROLS

**COOLTOUCH™ TRANSMITTER - FULL FUNCTION**

- 3 Forward Speeds & Motor Off
- Manual Reverse
- Lights On/Off with Full-Range Dimming

OPTIONAL CONTROLS

**WALL TRANSMITTER - FULL FUNCTION**

370038MULTR (Shown)

COORDINATING LIGHTING

To see the complete Hatteras Bay™ Collection visit Kichler.com.

Outdoor Wall
49064OZ



Outdoor Wall
49067OZ



BLADE SPECS

Blade Finish & Part Number
(Side 1) (Reversible)

Fan Finish



Cherry
B310101
GST



Walnut
FB310101
GST



GST
Galvanized
Steel



Cherry
B310101
TZP




Walnut
FB310101
TZP



TZP
Tannery
Bronze™
Powder Coat



Medium Walnut
FB310101
WCP



Dark Walnut
B310101
WCP




WCP
Weathered
Copper

HANGING MEASUREMENTS

WITH 12" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 22.50"	B: 18.50"	C: 14.00"	D: 6.75"



FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 11.25"	B: 7.25"	C: 14.00"	D: 6.75"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4025	53	76

AIR PERFORMANCE (FLUSH)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
3604	53	68