## INCLUDED FEATURES

## Blades (5) Included

- 14° Pitch
- 52" Sweep
- Reversible
- Wood

**Downrods** 6" and 12" Downrod with 1" (O.D.) *Note: Décor trim must be removed for use with 6" downrod.* 

**Downlight** Replaceable. Includes (4) E12, 40W, Krypton/T3 Lamps, 5907FST

Downlight Glass Fresnel Lens

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, with Optional Flush Mount Accessory 337008 on page 314. Note: Décor trim must be removed for use with Flush Mount.

**Control** CoolTouch™ Transmitter - Full Function

#### FAN FEATURES

Mounting Slope - Pitch 30° or 7/12

Lead Wire 78"

cUL Listed Indoor

Hanging Weight 31.6 lbs.

**Body Material** Steel

Warranty www.Kichler.com/Warranty

# MOTOR FEATURES

Motor Size/Type 188mm X 15mm, AC

Amps 0.52 on High

RPM 167 on High

Energy Star® No

## INCLUDED CONTROLS



## COOLTOUCH™ TRANSMITTER -FULL FUNCTION

- 3 Forward Speeds & Motor Off
- Manual Reverse
- Lights On/Off with Full-Range Dimming

#### OPTIONAL CONTROLS



WALL TRANSMITTER -FULL FUNCTION 370038MULTR (Shown)

# COORDINATING LIGHTING

To see the complete Kittery Point™ Collection visit Kichler.com.




42437AP

# HANGING MEASUREMENTS

#### WITH 6" DOWNROD

WITH O DOWNKOD					
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)		
<b>A:</b> 18.25"	<b>B:</b> 11.75"	C: 16.25"	<b>D:</b> 6.00"		



## WITH 12" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	<b>Housing</b> (width)	Ceiling Canopy (width)
<b>A:</b> 24.25"	<b>B:</b> 17.75"	<b>C:</b> 16.25"	<b>D:</b> 6.00"

AIR PERFORMANCE				
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt		
4664	62	75		

## **BLADE SPECS**

Blade Finish & Part Number (Side 1) (Reversible)

Fan Finish











