INCLUDED FEATURES

Blades (3) Included

- 12° Pitch
- 60" Sweep
- Non-reversible
- ABS

Downrods 6" Downrod with 1" (O.D.)

Downlight Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 80 CRI, 3,000K

Downlight Glass Frosted White Polycarbonate

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

Control 65K Wall Control - Full Function

FAN FEATURES

Mounting Slope - Pitch 30° or 7/12

Lead Wire 78"

cETL Listed Damp

Hanging Weight 21.5 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 188mm X 15mm, AC

Amps 0.60 on High

RPM 156 on High

Energy Star® No

INCLUDED CONTROLS



65K WALL CONTROL -FULL FUNCTION

- 3 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- Faceplates Included in 3 Colors

OPTIONAL CONTROLS



65K COOLTOUCH™ TRANSMITTER -FULL FUNCTION 370006 (Shown)

METAL CAPS

Includes a metal fixture cap for non-light use.









BLADE SPECS

Blade Finish & Part Number (Side 1) (Reversible)

Fan Finish


















HANGING MEASUREMENTS

WITH 6" DOWNROD

Fixture Drop	Blade Drop	Housing	Ceiling Canopy
(from ceiling)	(from ceiling)	(width)	(width)
A: 15.25"	B: 13.00"	C: 9.00"	D: 6.75"



AIR PERFORMANCE			
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt	
5797	72	81	



