INCLUDED FEATURES

Blades (5) Included - 12° Pitch - 52" Sweep - Non-reversible - ABS Downrods 4.5" Downrod with 1" (O.D.) Downlight N/A Downlight Glass N/A Optional Downlight See pages 318-320 Uplight N/A Uplight Glass N/A Low Ceiling Adaptable Yes, Low Ceiling Adaptable Control Pull Chain

FAN FEATURES

Mounting Slope – Pitch 30° or 7/12 Lead Wire 78" cUL Listed Wet Hanging Weight 19 lbs. Body Material ABS Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 172mm X 17mm, AC Amps 0.55 on High RPM 205 on High Energy Star[®] No

INCLUDED CONTROLS

PULL CHAIN

- 3 Speeds
- 3 Forward & Reverse
- Manual Reverse

OPTIONAL CONTROLS

65K WALL CONTROL SYSTEM -LIMITED FUNCTION 371042 (Shown) 371082



HANGING MEASUREMENTS

WITH 4.5" DOWNROD						
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)		† † АВ 	¢⊢
A: 14.25"	B: 11.75"	C: 12.50"	D: 5.75"		⊥.⊏	

Cubic Ft.

Per Minute

Per Watt

79

AIR PERFORMANCE							
AIRFLOW	POWER	AIRFLOW					
Cubic Ft.	USAGE	EFFICIENCY					

Watts on High

(Excludes

Lights)


65


Per Minute

on High

5116

W	C





CLIMATES[™]-grade fans are built with impressive corrosion-resistant materials to withstand harsh outdoor elements: extreme heat, saltwater spray, intense cold and constant UV exposure.