INCLUDED FEATURES

Blades (5) Included

- 12° Pitch
- 52" Sweep
- Non-reversible
- ABS

Downrods 4" Downrod with 3/4" (O.D.) Non-Threaded

Downlight N/A

Downlight Glass N/A

Optional Downlight See pages 318-320

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Dual

Mount Included

Control Pull Chain

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 15.6 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 153mm X 13mm, AC

Amps 0.48 on High

RPM 178 on High

Energy Star® No

INCLUDED CONTROLS

PULL CHAIN

- 3 Speeds
- 3 Forward & Reverse
- Manual Reverse



OPTIONAL CONTROLS



65K WALL CONTROL SYSTEM -LIMITED FUNCTION 371042 (Shown) 371082

SLOPE ADAPTER



For slope ceiling adapter, see page 316.

DOWNRODS

For Basics 400 Series Non-Threaded Downrods, see page 316.

BLADE SPECS

Blade Finish & Part Number (Side 1) (Reversible)

Fan Finish


















HANGING MEASUREMENTS

WITH 4" DOWNROD

	WITH 4 DOWNROD				
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)		
A: 12.25"	B: 10.25"	C: 11.00"	D: 5.25"		



FLUSH MOUNT

Fixture Drop	Blade Drop	Housing	Ceiling Canopy
(from ceiling)	(from ceiling)	(width)	(width)
A •9 00"	B • 7.00"	C: 11 00"	D· 5 25"



AIR PERFORMANCE AIRFLOW AIRFLOW **POWER** Cubic Ft. USAGE **EFFICIENCY** Per Minute Cubic Ft. Watts on High on High Per Minute (Excludes Per Watt Lights) 4286 56 75

AIR PERFORMANCE (FLUSH)			
POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt		
57	71		
	POWER USAGE Watts on High (Excludes Lights)		