

INCLUDED FEATURES

Blades (5) Included

- 12° Pitch
- 42" Sweep
- Non-reversible
- ABS

Downrods 4" Downrod with 3/4" (O.D.) Non-Threaded

Downlight N/A

Downlight Glass N/A

Optional Downlight See pages 318-320

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Dual Mount Included

Control Pull Chain

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 17.6 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type 153mm X 10mm, AC

Amps 0.42 on High

RPM 218 on High

Energy Star® No

INCLUDED CONTROLS

PULL CHAIN

- 3 Speeds
- 3 Forward & Reverse
- Manual Reverse



OPTIONAL CONTROLS



65K WALL CONTROL SYSTEM - LIMITED FUNCTION
371042 (Shown)
371082

SLOPE ADAPTER




For slope ceiling adapter, see page 316.

DOWNRODS

For Basics 400 Series Non-Threaded Downrods, see page 316.

BLADE SPECS


Blade Finish & Part Number (Side 1) **Fan Finish (Reversible)**



HANGING MEASUREMENTS

WITH 4" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 12.75"	B: 10.25"	C: 10.75"	D: 5.25"



FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 9.50"	B: 7.00"	C: 10.75"	D: 5.25"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
3034	49	62

AIR PERFORMANCE (FLUSH)

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
2832	49	57