

INCLUDED FEATURES

Blades (3) Included

- 14° Pitch
- 65" Sweep
- Non-reversible
- ABS

Downrods 6" Downrod with 1" (O.D.)

Downlight Replaceable. 23W Dimmable Integrated LED Platform, 2,300 Lumens, 3,000K

Downlight Glass White Polycarbonate Lens

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

Control 6-Speed DC Wall Control System

FAN FEATURES

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78"

cUL Listed Damp

Hanging Weight 26.4 lbs.

Body Material Steel

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type DC-188

Amps 0.44 on High

RPM 126 on High

Energy Star® No

INCLUDED CONTROLS



6-SPEED DC WALL CONTROL SYSTEM

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- No More Than Two Fans on One Circuit
- Faceplates Included in 3 Colors

OPTIONAL CONTROLS



DC COOLTOUCH™ TRANSMITTER - FULL FUNCTION 371075 (Shown)

COORDINATING LIGHTING

To see more from these collections visit Kichler.com.



Basford™ Pendant
43520DAG



Stelata™ Sconce
45627PN


BLADE SPECS

Blade Finish & Part Number (Side 1)	Fan Finish (Reversible)
Light Oak FB300365 MWH	MWH Matte White
Walnut FB300365 PN	PN Polished Nickel
Weathered White Walnut FB300365 SB	SBK Satin Black

HANGING MEASUREMENTS

WITH 6" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 14.50"	B: 11.75"	C: 10.00"	D: 6.25"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
9548	34	282

