

INCLUDED FEATURES

Blades (3) Included

- 20° Pitch
- 60" Sweep
- Non-reversible
- Polycarbonate

Downrods 6" Downrod with 1" (O.D.)

Downlight Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 3,000K

Downlight Glass Etched Cased Opal**Optional Downlight** N/A**Uplight** N/A**Uplight Glass** N/A**Low Ceiling Adaptable** No**Control** 6-Speed DC Wall Control System

FAN FEATURES

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78"

cUL Listed Indoor

Hanging Weight 23.4 lbs.

Body Material Polycarbonate

Warranty www.Kichler.com/Warranty

MOTOR FEATURES

Motor Size/Type DC-188mm X 10mm

Amps 0.47 on High

RPM 128 on High

Energy Star® No

INCLUDED CONTROLS

**6-SPEED DC WALL CONTROL SYSTEM**

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- No More Than Two Fans on One Circuit
- Faceplates Included in 3 Colors

OPTIONAL CONTROLS

**DC COOLTOUCH™ TRANSMITTER - FULL FUNCTION 371075 (Shown)**

BLADE SPECS

Blade Finish & Part Number
(Side 1) (Reversible)


Fan Finish



HANGING MEASUREMENTS

WITH 6" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 15.00"	B: 11.75"	C: 12.75"	D: 7.00"



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
7587	34	220

