## LED Downlights Generation I

Finish: White with Polycarbonate Diffuser



Kichler took the original small Generation I Low Profile LED Downlight and made it better. Offering the same domed diffuser and extending just 1.25" from the ceiling, the 43878 fixture now disperses 600 lumens of light and is T-24 compliant in all conditions. Damp rated for outdoor ceilings, this fixture is ideal for coastal environments. For installation efficiencies, the 43846 downlight is now available in 24-count bulk packs.

## LED Downlights - Generation I

	ITEM#	FINISH	LIGHT SOURCE	LED OUTPUT	DIMENSIONS	HCWO	NOTES
Α	43846	WHLED27, WHLED27B	(1) 15W 😂 💠 🧮	2700K, 90 CRI, 850 Lumens, 57 LPW	7.5W x 1.25H	3.75	© © Dimmable. Wet indoor ceiling, damp indoor wall. Item number with "B" signifies 24 count bulk pack.
В	43846	WHLED30, WHLED30B	(1) 15W 🔇 💠 🚟	3000K, 90 CRI, 850 Lumens, 57 LPW	7.5W x 1.25H	3.75	Dimmable. Wet indoor ceiling, damp indoor wall. Item number with "B" signifies 24 count bulk pack.
С	43878	WHLED27	(1) 11.5W 🕸 💠 ፭ *	2700K, 90 CRI, 600 Lumens, 54 LPW	6W x 1.25H	3	<b>™</b> Simmable. Wet indoor ceiling, damp indoor wall, damp outdoor ceiling.
D	43878	WHLED30	(1) 11.5W 😂 💠 🎫 *	3000K, 90 CRI, 600 Lumens, 54 LPW	6W x 1.25H	3	<b>™ ⑤ ®</b> * Dimmable. Wet indoor ceiling, damp indoor wall, damp outdoor ceiling.

Measurements shown in inches. U.S. & Canada Patent Pending. Delivered Lumens shown. \*Energy Star and Title 24 Designation in process. Refer to Kichler.com.