























# LED Downlights Generation II

Finish: Assorted with Polycarbonate Diffuser

|  |   |  |
|--|---|--|
| <p><b>2700K</b></p>  <p><b>E</b>   43848 NILED27<br/>43848 OZLED27<br/>43848 WHLED27</p>                                  | <p><b>3000K</b></p>  <p><b>F</b>   43848 NILED30<br/>43848 OZLED30<br/>43848 WHLED30</p>                                  |  <p><b>4146LED</b><br/>LED Retrofit for<br/>43848, 43846</p> |
| <p><b>2700K/Title 24</b></p>  <p><b>G</b>   43848 NILED27T<br/>43848 OZLED27T<br/>43848 WHLED27T<br/>43848 WHLED27TB</p> | <p><b>3000K/Title 24</b></p>  <p><b>H</b>   43848 NILED30T<br/>43848 OZLED30T<br/>43848 WHLED30T<br/>43848 WHLED30TB</p> |  |

The Kichler Low Profile LED Downlights – Generation II – feature a 7.5" total diameter to allow for recessed retrofit, but can also install in new construction utilizing any 3" or 4" ceiling J-box. The fixtures feature a domed diffuser to evenly disperse 1000 lumens of light, and extend just 1.25" from the ceiling. Offered in three finishes, these Low Profile LED Downlights are also available in a Title-24 compliant model (identified as those items with the T at the end).

## LED Downlights - Generation II

| ITEM #         | FINISH                                  | LIGHT SOURCE  | LED OUTPUT                         | DIMENSIONS   | HCWO | NOTES  |
|----------------|---|---|------------------------------------|--------------|------|--|
| <b>E</b> 43848 | NILED27, OZLED27, WHLED27               | (1) 15W    | 2700K, 90 CRI, 1000 Lumens, 67 LPW | 7.5W x 1.25H | 3.75 |   Dimmable. Wet indoor ceiling, damp indoor wall.  |
| <b>F</b> 43848 | NILED30, OZLED30, WHLED30               | (1) 15W    | 3000K, 90 CRI, 1000 Lumens, 67 LPW | 7.5W x 1.25H | 3.75 |   Dimmable. Wet indoor ceiling, damp indoor wall.  |
| <b>G</b> 43848 | NILED27T, OZLED27T, WHLED27T, WHLED27TB | (1) 15W    | 2700K, 90 CRI, 950 Lumens, 63 LPW  | 7.5W x 1.25H | 3.75 |    Dimmable. Wet indoor ceiling, damp indoor wall. Item number with "B" signifies 24 count bulk pack. |
| <b>H</b> 43848 | NILED30T, OZLED30T, WHLED30T, WHLED30TB | (1) 15W    | 3000K, 90 CRI, 950 Lumens, 63 LPW  | 7.5W x 1.25H | 3.75 |    Dimmable. Wet indoor ceiling, damp indoor wall. Item number with "B" signifies 24 count bulk pack. |

Delivered Lumens shown. Measurements shown in inches. U.S. & Canada Patent Pending.