

LED Ceiling

Long-life light emitting diodes (LED) provide an approximately 40,000-hour life span to L70 (70% initial lumens) – about 15 years of standard operation.

- True optics: pure white light and controlled beam spread with no fade or drop off of light
- High Color Rendering Index (CRI)
- Standard installation



A | 42380 NILEDR



A | 42380 OZLEDR



B | 42379 NILEDR



B | 42379 OZLEDR



C | 43883 NILEDR
Hatteras Bay™



C | 43883 OZLEDR
Hatteras Bay™



D | 8112 NILEDR



D | 8112 OZLEDR


















E | 8116 NILEDR



E | 8116 OZLEDR

LED Ceiling

ITEM #	FINISH	LIGHT SOURCE	LED OUTPUT	DIMENSIONS	NOTES
A	42380 NILEDR, OZLEDR	(1) 22W  	3000K, 90 CRI, 1675 Lumens, 76 LPW	14W x 3.25H	 Dimmable.
B	42379 NILEDR, OZLEDR	(1) 22W  	3000K, 90 CRI, 1675 Lumens, 76 LPW	13.25W x 3.25H	 Dimmable.
C	43883 NILEDR, OZLEDR	(1) 22W  	3000K, 90 CRI, 1675 Lumens, 76 LPW	13.25W x 4.5H	 Dimmable.
D	8112 NILEDR, OZLEDR	(1) 22W  	3000K, 90 CRI, 1675 Lumens, 76 LPW	13.25W x 6H	 Dimmable.
E	8116 NILEDR, OZLEDR	(1) 22W  	3000K, 90 CRI, 1675 Lumens, 76 LPW	15.25W x 6.5H	 Dimmable.

Measurements shown in inches. U.S. & Canada Patent Pending.