

Directional Rail Lights



A | 10326 NI



B | 7772 NI
Hendrik™



B | 7772 OZ
Hendrik™



C | 42589 BK
Solstice



D | 42164 AP
Ballamy™

Directional Rail Lights

ITEM #	FINISH	LIGHT SOURCE	LED OUTPUT	DIMENSIONS	STEM TILT	EXT.	HCWO	NOTES
A	10326	NI	(4) 25W 2700K, 80 CRI, 1000 Lumens, 40 LPW	35.25W x 11.5H x 35.25L	---	10.5	3	Dimmable. 90° vertical rotation, 330° horizontal rotation. May be installed on ceiling or wall.
B	7772	NI, OZ	(4) 50W (GU10)	5W x 8.25H x 30L	90°	6.25	4	Ⓧ May be installed on ceiling or wall.
C	42589	BK	(4) 50W (GU10)	4W x 8.25H x 32L	---	6.25	2.25	Ⓧ May be installed on ceiling or wall, vertically or horizontally.
D	42164	AP	(4) 50W (GU10)	5.5W x 8.75H x 34.25L	---	7.5	2.75	Ⓧ 90° vertical rotation, 330° horizontal rotation. May be installed on ceiling or wall.

Measurements shown in inches. U.S. & Canada Patent Pending: C.