

# LED Wall Sconces

Kichler® LED lighting exceeds the standards for reliability and beauty.

- Long-life light emitting diodes (LED) provide approximately 40,000-hour life span to L70 (70% initial lumens) - about 15 years of standard operation
- True optics: pure white light and controlled beam spread with no fade or drop off of light
- High Color Rendering Index (CRI)
- Standard installation



**A** | 10630 PNLED  
Arcola™ LED



**B** | 42372 NILED  
Vego LED



**C** | 10438 NCHLED  
Santiago LED



**D** | 10439 NCHLED  
Santiago LED



**E** | 45686 NBRLED  
Indeco™ LED



**E** | 45686 PNLED  
Indeco™ LED



**F** | 42500 PNLED  
Jewel LED



**G** | 10620 NILED  
Nobu LED



**H** | 10421 SNLED  
Rigel LED

## LED Wall Sconces

ITEM #	FINISH	LIGHT SOURCE	LED OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES	
A	10630	PNLED	(1) 16W	3000K, 90 CRI, 770 Lumens, 49 LPW	15W x 5.5H	4	2.75	Dimmable.
B	42372	NILED	(1) 20W	3000K, 90 CRI, 300 Lumens, 15 LPW	5W x 12H	3	6	Dimmable. May be installed vertically or horizontally.
C	10438	NCHLED	(1) 8W	3000K, 90 CRI, 420 Lumens, 58 LPW	5.5W x 14.25H	3.75	5.25	Dimmable.
D	10439	NCHLED	(1) 16W	3000K, 90 CRI, 880 Lumens, 55 LPW	11W x 14.25H	3.75	5.25	Dimmable.
E	45686	NBRLED, PNLED	(1) 16W	3000K, 90 CRI, 1090 Lumens, 68 LPW	5W x 14.5H	3.75	12	Dimmable. May be installed with glass up or down. May be installed vertically or horizontally.
F	42500	PNLED	(1) 20W	3000K, 90 CRI, 225 Lumens, 12 LPW	6.5W x 20H	3.75	6	Dimmable. May be installed with glass up or down.
G	10620	NILED	(1) 16W	3000K, 90 CRI, 790 Lumens, 51 LPW	13W x 9.5H	4	5	Dimmable.
H	10421	SNLED	(1) 16W	3000K, 90 CRI, 910 Lumens, 57 LPW	12W x 10H	4	5	Dimmable.
J	11315	NILED, OZLED	(2) 22W	3000K, 90 CRI, 1380 Lumens, 63 LPW	7W x 16H	3.75	8	Dimmable.
K	11319	NILED, OZLED	(1) 15W	3000K, 90 CRI, 960 Lumens, 66 LPW	9.5W x 10.75H	3.75	5.25	Dimmable.

Measurements shown in inches. U.S. & Canada Patent Pending.