



J | 11315 NILED
Pro Solutions LED



J | 11315 OZLED
Pro Solutions LED



K | 11319 NILED
Pro Solutions LED



K | 11319 OZLED
Pro Solutions LED



L | 44162 CLPLED
Serene LED



L | 44162 NBRLED
Serene LED



M | 45656 CHLED
Trinsic™ LED



N | 45876 PNLED
Bordeaux LED



O | 10795 NILED
LED



P | 10797 NILED
LED



Q | 10790 NILED
LED



Q | 10790 OZLED
LED



R | 11131 AZTLED
LED



S | 11132 AZTLED
LED



T | 11134 AZTLED
LED



U | 11135 AZTLED
LED

LED Wall Sconces

ITEM #	FINISH	LIGHT SOURCE	LED OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
L	44162 CLPLED, NBRLED	(1) 16W	3000K, 90 CRI, Lumens, LPW	6.5W x 17H	3.5	7.25	Dimmable.
M	45656 CHLED	(1) 30W	3000K, 90 CRI, 400 Lumens, 13 LPW	4.5W x 12H x 3.5L	3.5	---	
N	45876 PNLED	(1) 15.5W	3000K, 90 CRI, 465 Lumens, 60 LPW	4.5W x 13.75H	3.75	10.25	May be installed vertically or horizontally.
O	10795 NILED	(1) 16W	3000K, 90 CRI, 910 Lumens, 58 LPW	11W x 11.75H	4	6	Dimmable.
P	10797 NILED	(1) 16W	3000K, 90 CRI, 870 Lumens, 55 LPW	8.25W x 8H	3.5	4.75	Dimmable.
Q	10790 NILED, OZLED	(1) 15W	3000K, 90 CRI, 900 Lumens, 60 LPW	11.75W x 6H	3.5	2.5	Dimmable.
R	11131 AZTLED	(1) 15W	3000K, 90 CRI, 840 Lumens, 56 LPW	9W x 2.75H	2.75	4.5	Dimmable. May be installed on wall or ceiling.
S	11132 AZTLED	(1) 23W	3000K, 90 CRI, 1220 Lumens, 53 LPW	11W x 3H	3	5.5	Dimmable. May be installed on wall or ceiling.
T	11134 AZTLED	(1) 15W	3000K, 90 CRI, 740 Lumens, 49 LPW	9W x 3.25H	3.25	4.5	Dimmable. May be installed on wall or ceiling.
U	11135 AZTLED	(1) 23W	3000K, 90 CRI, 1060 Lumens, 46 LPW	11W x 3.5H	3.5	5.5	Dimmable. May be installed on wall or ceiling.

Measurements shown in inches. U.S. & Canada Patent Pending.