



Wall Sconces

ITEM #	FINISH	LIGHT SOURCE	LED BULB OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
G	44079 BK	(2) 60W (C) ✓	---	7.5W x 12H	3.75	6	Ⓧ Ⓡ
H	10630 PN	(1) 18W (GU24)	---	15W x 5.5H	4	2.5	Ⓧ Ⓡ
J	45568 NI, OZ	(1) 100W (M)	---	5.5W x 10.75H	7.25	5.5	Ⓧ May be installed with glass up or down.
J	45568 NIL16, OZL16	(1) 9W (M) Ⓡ Ⓡ	3000K, 80 CRI, 800 Lumens, LPW	5.5W x 10.75H	7.25	5.5	Ⓧ May be installed with glass up or down.
K	45770 PN	(1) 100W (M)	---	5W x 8H	6.5	2.5	Ⓧ
L	45866 CH, NBR	(1) 75W (M)	---	4.75W x 10H	6.25	4.5	Ⓧ May be installed with glass up or down.
M	45457 CH, CLP, OZ	(1) 60W (M)	---	5W x 9.5H	5.75	6	Ⓧ
N	44091 BK	(2) 60W (M)	---	4.75W x 20.75H	4	10.5	Ⓧ May be installed on wall or ceiling, vertically or horizontally.
O	45576 NI, OZ	(1) 100W (M)	---	5W x 11.5H	6.25	6	Ⓧ
P	45938 NI, OZ	(1) 100W (M)	---	6.5W x 10.75H	8.75	5	Ⓧ May be installed with glass up or down.
P	45938 NIL16, OZL16	(1) 9W (M) Ⓡ Ⓡ	3000K, 80 CRI, 800 Lumens, LPW	6.5W x 10.75H	8.75	5	Ⓧ Dimmable. May be installed with glass up or down.

Measurements shown in inches. U.S. & Canada Patent Pending.