

Langford™

Finish: **Brushed Nickel or Olde Bronze®**

Glass: **Satin Etched White**



B | 5389 NI, OZ
5389 NIL16, OZL16



A | 5388 NI, OZ
5388 NIL16, OZL16
Wall Sconce



C | 5390 NI, OZ
5390 NIL16, OZL16



D | 5391 NI, OZ
5391 NIL16, OZL16

Coordinating



1783 NI, OZ

Features











Mounts Up or Down

Finishes



Langford™

	ITEM #	FINISH	LIGHT SOURCE	LED BULB OUTPUT	DIMENSIONS	EXT.	HCWO	NOTES
A	5388	NI, OZ	(1) 100W (M)	---	7.25W x 7.75H	8.25	4.5	Ⓚ May be installed with glass up or down.
A	5388	NIL16, OZL16	(1) 9W (M)  	3000K, 80 CRI, 800 Lumens, LPW	7.25W x 7.75H	8.25	4.5	Ⓚ Dimmable. May be installed with glass up or down.
B	5389	NI, OZ	(2) 100W (M)	---	17.5W x 8.5H	8.25	6.25	Ⓚ May be installed with glass up or down.
B	5389	NIL16, OZL16	(2) 9W (M)  	3000K, 80 CRI, 800 Lumens, LPW	17.5W x 8.5H	8.25	6.25	Ⓚ Dimmable. May be installed with glass up or down.
C	5390	NI, OZ	(3) 100W (M)	---	26.25W x 8.5H	8.25	6.25	Ⓚ May be installed with glass up or down.
C	5390	NIL16, OZL16	(3) 9W (M)  	3000K, 80 CRI, 800 Lumens, LPW	26.25W x 8.5H	8.25	6.25	Ⓚ Dimmable. May be installed with glass up or down.
D	5391	NI, OZ	(4) 100W (M)	---	35W x 8.5H	8.25	6.25	Ⓚ May be installed with glass up or down.
D	5391	NIL16, OZL16	(4) 9W (M)  	3000K, 80 CRI, 800 Lumens, LPW	35W x 8.5H	8.25	6.25	Ⓚ Dimmable. May be installed with glass up or down.

Measurements shown in inches. U.S. & Canada Patent Pending.