





LED Accent - 3.5W

Finishes	BKT (shown), AZT, CBR		Additional Finishes
Color Temperature	2700K - Warm White	3000K - Pure White	 AZT  CBR
Item Number by Beam Spread and Finish	10° Spot 16153 AZT27, 16153 BKT27, 16153 CBR27 35° Flood 16154 AZT27, 16154 BKT27, 16154 CBR27 60° Wide Flood 16155 AZT27, 16155 BKT27, 16155 CBR27	10° Spot 16153 AZT30, 16153 BKT30, 16153 CBR30 35° Flood 16154 AZT30, 16154 BKT30, 16154 CBR30 60° Wide Flood 16155 AZT30, 16155 BKT30, 16155 CBR30	
Housing	Cast Aluminum or Cast Brass (CBR)		
Wattage/VA, Delivered Lumens & Efficacy	3.5W, 5.25VA	300 lm, 86 lm/W	<i>Lumen levels are the same for 2700K and 3000K</i>
CRI	80+		
Voltage Range	9V-15V AC/DC with no loss in light output. 4kV (4000 volt protection).		
Light Source	6 integrated high-output LEDs with 3-step binning for color consistency. Custom T.I.R. (Total Internal Reflection) acrylic lens. Tested to a Lumen Maintenance L70 of 40,000 hrs.		
Wiring	48" of usable #18-2, SPT-1W leads		
Notes	Replaces the equivalent of a 35W Halogen. Includes 8" slotted in-ground stake and 2 gel-filled wire nuts. Brass will naturally patina over time.		
Accessories	Mounting: 15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15609 Junction Box Mounting Bracket 15647, 15514 90° Elbow 15649 Stem Coupler 15645, 15656, 15657, 15658, 15570 Stems 15509, 15510, 15511, 15512, 15513 Stems (CBR) 15515 Two Fixture Mount (CBR)	15493 Round Mounting Base (CBR) Cowls & Lenses: 16074 Long Cowl 15875 AMB Amber Lens 15875 HGRN Holiday Green Lens 15875 RD Red Lens 15885 GRN Green Foliage Lens 15895 FRO Frosted Lens	
Dimensions	 