



	Wall Wash			Wall Wash Accent			
Finishes	BBR (shown), AZT, BKT		Available Finishes	BBR (shown), AZT, BKT		Available Finishes	
Color Temperature	2700K - Warm White	3000K - Pure White	 AZT  BKT	2700K - Warm White	3000K - Pure White	 AZT  BKT	
Item Number and Finish	16070 AZT27R 16070 BBR27R 16070 BKT27R	16070 AZT30R 16070 BBR30R 16070 BKT30R		15861 AZT27R 15861 BBR27R 15861 BKT27R	15861 AZT30R 15861 BBR30R 15861 BKT30R		
Housing	Cast Aluminum or Cast Brass (BBR)			Cast Aluminum or Cast Brass (BBR)			
Power Usage at 12V AC Input, VA and Watts	4.3W, 5.8VA			4.3W, 5.8VA			
Color Temp. & CRI	2700K 80+	3000K 80+		2700K 80+	3000K 80+		
Voltage Range	9V-15V AC/DC with no loss in light output			9V-15V AC/DC with no loss in light output			
Light Source	8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.			8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.			
Delivered Lumens & Efficacy	2700K=294 lm 2700K=67 lm/W	3000K=302 lm 3000K=73 lm/W		2700K=294 lm 2700K=67 lm/W	3000K=302 lm 3000K=73 lm/W		
Wiring	35" of usable #18-2, SPT-1W leads. Wire connectors supplied.			64" of usable #18-2, SPT-1W leads. Wire connectors supplied.			
Notes	Beam spread vertical of 80°, horizontal of 100°. Includes 8" slotted in-ground stake. Fully adjustable knuckle. Brass will naturally patina over time.			Beam spread vertical of 108°, horizontal of 111°. Includes 8" slotted in-ground stake. Fully adjustable knuckle. Brass will naturally patina over time.			
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15609 Junction Box Mounting Bracket 15647 90° Elbow 15645, 15656, 15657, 15658, 15570 Stems			15601 Surface Mounting Flange 15607 Surface Mounting Bracket 15647 90° Elbow 15645, 15656, 15657, 15658, 15570 Stems			
Dimensions							
Photometrics							
Distance from Wall	0'	.5'	1'	2'	3'	4'	5'
2'	47	39.4	16.2	1.3	.25	.22	.19
4'	12.5	12	10.8	5.1	1.8	.54	.17
	0'	.5'	1'	2'	3'	4'	5'
	51.2	45.5	30	7.1	1.9	.68	.30
	12.9	12.9	11.8	7.9	4.2	1.6	.7