

In-Ground

Integrated LED



	LED In-Ground – 4W		LED In-Ground – 6.5W		LED In-Ground – 14W	
Finishes	BBR		BBR		BBR	
Color Temperature	2700K - Warm White	3000K - Pure White	2700K - Warm White	3000K - Pure White	2700K - Warm White	3000K - Pure White
Item Number and Finish	10° Spot 16030 BBR27	10° Spot 16030 BBR30	10° Spot 16033 BBR27	10° Spot 16033 BBR30	10° Spot 16036 BBR27	10° Spot 16036 BBR30
	35° Flood 16031 BBR27	35° Flood 16031 BBR30	35° Flood 16034 BBR27	35° Flood 16034 BBR30	35° Flood 16037 BBR27	35° Flood 16037 BBR30
	60° Wide Flood 16032 BBR27	60° Wide Flood 16032 BBR30	60° Wide Flood 16035 BBR27	60° Wide Flood 16035 BBR30	60° Wide Flood 16038 BBR27	60° Wide Flood 16038 BBR30
Housing	Cast Brass					
Power Usage at 12V AC Input, VA and Watts	4W, 5.8VA		6.5W, 9.3VA		14W, 18.5VA	
CRI	80+					
Voltage Range	9V-15V AC/DC with no loss in light output					
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		5 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		5 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.	
Delivered Lumens & Efficacy	2700K = 146 lm 2700K = 37 lm/W	3000K = 170 lm 3000K = 43 lm/W	2700K = 306 lm 2700K = 47 lm/W	3000K = 348 lm 3000K = 54 lm/W	2700K = 520 lm 2700K = 37 lm/W	3000K = 590 lm 3000K = 42 lm/W
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed.					
Notes	Includes anti-heaving, auger-style in-ground stake. Drive-over and walk-over rated for 4500 lb. car or truck. Aimable up to 15° on the vertical. Compares to MR16 20W Halogen. Corrosion-free, all-brass construction. Brass will naturally patina over time.		Includes anti-heaving, auger-style in-ground stake. Drive-over and walk-over rated for 4500 lb. car or truck. Aimable up to 15° on the vertical. Compares to MR16 35W Halogen. Corrosion-free, all-brass construction. Brass will naturally patina over time.		Includes anti-heaving, auger-style in-ground stake. Drive-over and walk-over rated for 4500 lb. car or truck. Aimable up to 15° on the vertical. Compares to MR16 50W Halogen. Corrosion-free, all-brass construction. Brass will naturally patina over time.	
Accessories	16501 BBRP Concrete Kit. See page 176 for Rock Guard and Cowl options.					

Dimensions

