

2-in-1 Water Accent

Integrated LED



2-in-1 Water Accent

Finishes	SS					
Color Temperature	2700K - Warm White		3000K - Pure White		4200K - Cool White	
Item Number and Finish	15711 SS27		15711 SS		15711 SS42	
Housing	Stainless Steel housing with integrated cowl					
Power Usage at 12V AC Input VA and Watts	3.4W, 4.9VA					
Color Temp. & CRI	2700K, 80+		3000K, 80+		4200K, 80+	
Voltage Range	9V-15V AC/DC with no loss in light output					
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hours.					
Delivered Lumens & Efficacy	2700K = 135 lm 2700K = 40 lm/W		3000K = 150 lm 3000K = 44 lm/W		4200K = 180 lm 4200K = 53 lm/W	
Wiring	25' of usable #18-2, SPT-2W leads					
Notes	Custom reflector optics. Filled and sealed with two types of premium encapsulant to ensure fixture is completely watertight, 1/4-20 threaded mounting tap. Can also be used out of water as a mini accent light. Not recommended for use in salt water.					
Accessories	15776 BK Multi-fixture weighted base 15777 SS Out-of-water bracket 15778 BK Single fixture weighted base					
Dimensions						
Photometrics						
Distance from Source (ft.)	4'	8'	16'	24'	32'	40'
Illuminance (Foot-candles)	5.6	1.5	.4	.2	.1	.1
Beam Width (ft.)	3.3'	6.5'	13'	19.5'	26'	32.5'