

Path & Spread

12V Integrated LED



	Round Tiered			Flare					
Finishes	AGZ (shown), BKT, CW		Additional Finishes	AZT (shown), BBR, CO		Additional Finishes			
Color Temperature	2700K - Warm White	3000K - Pure White		2700K - Warm White	3000K - Pure White				
Item Number and Finish	16124 AGZ27 16124 BKT27 16124 CW27	16124 AGZ30 16124 BKT30 16124 CW30		16125 AZT27 16125 BBR27 16125 CO27	16125 AZT30 16125 BBR30 16125 CO30				
Housing	Aluminum			Cast Aluminum, Cast Brass (BBR) or Copper					
Power Usage at 12V AC Input, VA and Watts	3.8W, 4.95VA			4.3W, 5.8VA					
CRI	80+			80+					
Voltage Range	9V-15V AC/DC with no loss in light output			9V-15V AC/DC with no loss in light output					
Light Source	3 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.			8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.					
Delivered Lumens & Efficacy	2700K = 168 lm 2700K = 46 lm/W	3000K = 182 lm 3000K = 46 lm/W		2700K = 168 lm 2700K = 46 lm/W	3000K = 182 lm 3000K = 46 lm/W				
Wiring	30" of usable #18-2, SPT-1W leads. Cable connectors supplied.			30" of usable #18-2, SPT-1W leads. Cable connectors supplied.					
Notes	Includes 8" slotted in-ground stake and features decorative light-leak pattern			Includes 8" slotted in-ground stake. Copper and brass will naturally patina over time. Included reflector can be removed if necessary.					
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket			15601 Surface Mounting Flange 15607 Surface Mounting Bracket FM127265 Hexcell Louver FM128296BKT Glare Guard Reflector					
Dimensions									
Photometrics									
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Foot-candles (FC)	7.4	4.3	1.2	.21	.16	.14	.07	.03	.03
FC with Included Reflector*	-	17.5	5.8	2.4	1.2	.8	.5	.3	.1

*Using optional black glare guard reflector (FM128289BKT) will slightly reduce the above. Reflectors can be flipped or inverted for even more glare control