



	Petal		Pierced Dome						
	AZT		AZT						
Finishes	AZT		AZT						
Color Temperature	2700K - Warm White	3000K - Pure White	2700K - Warm White	3000K - Pure White					
Item Number and Finish	16126 AZT27	16126 AZT30	15857 AZT27R	15857 AZT30R					
Housing	Aluminum		Cast Aluminum						
Power Usage at 12V AC Input, VA and Watts	3.8W, 4.95VA		3.8W, 4.95VA						
CRI	80+		80+						
Voltage Range	9V-15V AC/DC with no loss in light output		9V-15V AC/DC with no loss in light output						
Light Source	3 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		3 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.						
Delivered Lumens & Efficacy	2700K = 168 lm 2700K = 46 lm/W	3000K = 182 lm 3000K = 46 lm/W	2700K = 168 lm 2700K = 46 lm/W	3000K = 182 lm 3000K = 49 lm/W					
Wiring	30" of usable #18-2, SPT-1W leads. Cable connectors supplied.		30" of usable #18-2, SPT-1W leads. Cable connectors supplied.						
Notes	Includes 8" slotted in-ground stake and features decorative light-leak pattern. AZT finish overlay with TZT undertone.		Includes 8" slotted in-ground stake and features decorative light-leak pattern. Incandescent version of fixture 15457 on page 143.						
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket								
Dimensions									
Photometrics									
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Foot-candles (FC)	12	6	1.6	.4	.16	.05	.02	.02	.01
	7.5	3.8	1.3	.3	.15	.02	.01	-	-