



Path & Spread

12V Integrated LED



Shepherd's Crook

Finishes	BBR (shown), AZT		Additional Finishes
Color Temperature	2700K - Warm White	3000K - Pure White	 AZT
Item Number and Finish	15807 AZT27R 15807 BBR27R	15807 AZT30R 15807 BBR30R	
Housing	Cast Aluminum or Brass (BBR)		
Power Usage at 12V AC Input, VA and Watts	4.3W, 5.8VA		
CRI	80+		
Voltage Range	9V-15V AC/DC with no loss in light output		
Light Source	8 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		
Delivered Lumens & Efficacy	2700K = 294 lm 2700K = 67 lm/W	3000K = 302 lm 3000K = 73 lm/W	
Wiring	24" of usable #18-2, SPT-1W leads. Cable connectors supplied.		
Notes	Includes 8" slotted in-ground stake. Brass will naturally patina over time.		
Accessories	15601 Surface Mounting Flange 15607 Surface Mounting Bracket		

Dimensions		
Photometrics		

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Foot-candles (FC)	61.9	53.5	11.96	2.47	1.04	.33	.22	.1	.08