

Deck & Patio

12V Integrated LED



	Vintage Park™		Decorative Hammered Roof											
Finishes	T _Z T		T _Z T											
Color Temperature	2700K - Warm White	3000K - Pure White	2700K - Warm White	3000K - Pure White										
Item Number and Finish	15750 T _Z T27R	15750 T _Z T30R	15763 T _Z T27R	15763 T _Z T30R										
Housing	Cast Aluminum		Brass											
Power Usage at 12V AC Input, VA and Watts	.86W, 1.86VA		.86W, 1.86VA											
CRI	80+	80+	80+	80+										
Voltage Range	9V-15V AC/DC with no loss in light output		9V-15V AC/DC with no loss in light output	Coordinating Products  LED Path Lights 15871 & 15843 , see page 44										
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.											
Delivered Lumens & Efficacy	2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W	2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W										
Wiring	72" of usable #18-2, SPT-1W leads. Cable connectors supplied.		72" of usable #18-2, SPT-1W leads. Cable connectors supplied.											
Notes	Includes stainless steel mounting bracket and hardware.		Features decorative light-leak pattern. Includes stainless steel mounting bracket and hardware. Brass will naturally patina over time.											
Dimensions														
Photometrics														
Mounting Height	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'
6"	76.5	20	3	.2	.06	.05	.03	76.5	20	3	.2	.06	.05	.03
12"	13	10.63	4.8	1.1	.20	.08	.05	13	10.63	4.8	1.1	.20	.08	.05
30"	3.2	3.4	2.6	1.2	.52	.24	.12	3.2	3.4	2.6	1.2	.52	.24	.12