









	Mini Deck Light			Half Moon										
Finishes	BBR (shown), AZT, BKT, WHT		Additional Finishes	BBR (shown), AZT, WHT		Additional Finishes								
Color Temperature	2700K - Warm White	3000K - Pure White	 AZT  BKT  WHT	2700K - Warm White	3000K - Pure White	 AZT  WHT								
Item Number and Finish	15765 AZT27R 15765 BBR27R 15765 BKT27R 15765 WHT27R	15765 AZT30R 15765 BBR30R 15765 BKT30R 15765 WHT30R		15764 AZT27R 15764 BBR27R 15764 WHT27R	15764 AZT30R 15764 BBR30R 15764 WHT30R									
Housing	Cast Aluminum or Cast Brass (BBR)			Cast Aluminum or Cast Brass (BBR) with satin-etched lens										
Power Usage at 12V AC Input, VA and Watts	.86W, 1.86VA		.86W, 1.86VA											
CRI	80+	80+	80+		80+									
Voltage Range	9V-15V AC/DC with no loss in light output		Coordinating Products	9V-15V AC/DC with no loss in light output										
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		 LED Path Lights 15815, 15827 & 15826, see pages 49-50	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.										
Delivered Lumens & Efficacy	2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W		2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W									
Wiring	72" of usable #18-2, SPT-1W leads. Cable connectors supplied.		72" of usable #18-2, SPT-1W leads. Cable connectors supplied.											
Notes	Includes stainless steel mounting bracket and hardware. White finish has coordinating white color leads. Brass will naturally patina over time.			Includes stainless steel mounting bracket and hardware. White finish has coordinating white color leads. Brass will naturally patina over time.										
Dimensions														
Photometrics														
Mounting Height	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'
6"	76.5	20	3	.2	.06	.05	.03	29.7	14.8	1.6	.07	.05	.01	.00
12"	13	10.63	4.8	1.1	.20	.08	.05	8.3	6.4	2.6	.45	.08	.02	.01
30"	3.2	3.4	2.6	1.2	.52	.24	.12	2.1	2.05	1.55	.5	.3	.11	.09