







	Overlay		Perforated											
Finishes	AZT (shown)		AZT (shown), CO, TZT		Additional Finishes									
Color Temperature	2700K - Warm White	3000K - Pure White	2700K - Warm White	3000K - Pure White	 CO									
Item Number and Finish	16112 AZT27	16112 AZT30	16113 AZT27 16113 CO27 16113 TZT27	16113 AZT30 16113 CO30 16113 TZT30										
Housing	Cast Aluminum		Cast Aluminum or Copper (CO)		 TZT									
Power Usage at 12V AC Input, VA and Watts	.86W, 1.86VA		.86W, 1.86VA											
CRI	80+	80+	80+	80+										
Voltage Range	9V-15V AC/DC with no loss in light output		Coordinating Product	9V-15V AC/DC with no loss in light output										
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.		 LED Path Lights 16122 see page 55	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.										
Delivered Lumens & Efficacy	2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W		2700K = 41 lm 2700K = 50 lm/W	3000K = 43 lm 3000K = 51 lm/W	 LED Path Lights 16123 see page 55								
Wiring	72" of usable #18-2, SPT-1W leads. Cable connectors supplied.		72" of usable #18-2, SPT-1W leads. Cable connectors supplied.											
Notes	Features decorative light-leak pattern with TZT underlay		Features decorative light-leak pattern. Copper will naturally patina over time.											
Dimensions														
Photometrics														
Mounting Height	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'
6"	14.5	7.1	.24	.02	.01	.00	.00	14.3	8.6	.19	.02	.01	.00	.00
12"	3.0	3.1	1.6	.08	.01	.01	.00	3.40	3.70	1.90	.05	.01	.00	.00
30"	.8	.87	.78	.4	.15	.03	.01	0.89	1.03	0.95	.45	.09	.01	.00