

Deck & Patio

12V Integrated LED



	Brick Light (with Louvers)				Brick Light (without Louvers)																																																																			
Finishes	AZT (shown)				AZT (shown)																																																																			
Color Temperature	2700K - Warm White		3000K - Pure White		2700K - Warm White		3000K - Pure White																																																																	
Item Number and Finish	15773 AZT27R		15773 AZT30R		15774 AZT27R		15774 AZT30R																																																																	
Housing	Cast Aluminum				Cast Aluminum																																																																			
Power Usage at 12V AC Input, VA and Watts	1.72 W, 3.72 VA				1.72 W, 3.72 VA																																																																			
CRI	80+	80+		80+		80+		80+																																																																
Voltage Range	9V-15V AC/DC with no loss in light output				9V-15V AC/DC with no loss in light output																																																																			
Light Source	2 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.				2 integrated high-output LEDs with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.																																																																			
Delivered Lumens & Efficacy	2700K = 82 lm 2700K= 100 lm/W		3000K = 86 lm 3000K = 102 lm/W		2700K = 82 lm 2700K= 100 lm/W		3000K = 86 lm 3000K = 102 lm/W																																																																	
Wiring	Wire connection must be made inside fixture				Wire connection must be made inside fixture																																																																			
Notes	Included stainless steel mounting hardware and junction box. Designed to be integrated into brick wall during construction. LED version is also usable in vertical risers. Incandescent version of fixture 15073 on page 162.				Included stainless steel mounting hardware and junction box. Designed to be integrated into brick wall during construction. LED version is also usable in vertical risers. Incandescent version of fixture 15074 on page 162.																																																																			
Dimensions																																																																								
Photometrics	<table border="1"> <tr> <td>Mounting Height</td> <td>0'</td><td>.5'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td> </tr> <tr> <td>12"</td> <td>.07</td><td>.40</td><td>1.3</td><td>.60</td><td>.14</td><td>.06</td><td>.03</td> </tr> <tr> <td>24"</td> <td>.02</td><td>.05</td><td>.16</td><td>.23</td><td>.23</td><td>.08</td><td>.05</td> </tr> <tr> <td>36"</td> <td>.01</td><td>.01</td><td>.83</td><td>.08</td><td>.11</td><td>.13</td><td>.08</td> </tr> </table>				Mounting Height	0'			.5'	1'	2'	3'	4'	5'	12"	.07	.40	1.3	.60	.14	.06	.03	24"	.02	.05	.16	.23	.23	.08	.05	36"	.01	.01	.83	.08	.11	.13	.08	<table border="1"> <tr> <td>Mounting Height</td> <td>0'</td><td>.5'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td> </tr> <tr> <td>12"</td> <td>3.00</td><td>1.30</td><td>0.10</td><td>0.44</td><td>0.10</td><td>0.03</td><td>0.03</td> </tr> <tr> <td>24"</td> <td>0.06</td><td>0.20</td><td>0.30</td><td>0.20</td><td>0.10</td><td>0.08</td><td>0.04</td> </tr> <tr> <td>36"</td> <td>0.04</td><td>0.09</td><td>0.10</td><td>0.18</td><td>0.12</td><td>0.09</td><td>0.06</td> </tr> </table>				Mounting Height	0'	.5'	1'	2'	3'	4'	5'	12"	3.00	1.30	0.10	0.44	0.10	0.03	0.03	24"	0.06	0.20	0.30	0.20	0.10	0.08	0.04	36"	0.04	0.09	0.10	0.18	0.12
Mounting Height	0'	.5'	1'	2'	3'	4'	5'																																																																	
12"	.07	.40	1.3	.60	.14	.06	.03																																																																	
24"	.02	.05	.16	.23	.23	.08	.05																																																																	
36"	.01	.01	.83	.08	.11	.13	.08																																																																	
Mounting Height	0'	.5'	1'	2'	3'	4'	5'																																																																	
12"	3.00	1.30	0.10	0.44	0.10	0.03	0.03																																																																	
24"	0.06	0.20	0.30	0.20	0.10	0.08	0.04																																																																	
36"	0.04	0.09	0.10	0.18	0.12	0.09	0.06																																																																	