



		Mini Step Light (with Louvers)				Mini Step Light (without Louvers)									
Finishes	<b>CO (shown), AZT, BBR, BKT, WHT</b>				Additional Finishes		<b>AZT (shown)</b>								
Color Temperature	2700K - Warm White		3000K - Pure White		 <b>AZT</b>	 <b>BBR</b>	2700K - Warm White		3000K - Pure White						
Item Number and Finish	<b>15782 AZT27R</b> <b>15782 BBR27R</b> <b>15782 BKT27R</b> <b>15782 CO27R</b> <b>15782 WHT27R</b>		<b>15782 AZT30R</b> <b>15782 BBR30R</b> <b>15782 BKT30R</b> <b>15782 CO30R</b> <b>15782 WHT30R</b>				<b>15780 AZT27R</b> <b>15780 AZT30R</b>								
Housing	Aluminum, Brass or Copper with white reflector. Zinc-plated steel housing.				Aluminum with white reflector. Zinc-plated steel housing.										
Power Usage at 12V AC Input, VA and Watts	.86W, 1.86VA				.86W, 1.86VA										
CRI	80+	80+			 <b>WHT</b>	 <b>BKT</b>	80+	80+							
Voltage Range	9V-15V AC/DC with no loss in light output						9V-15V AC/DC with no loss in light output								
Light Source	1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.				1 integrated high-output LED with 3-step binning for color consistency. Tested to a Lumen Maintenance L70 of 40,000 hrs.										
Delivered Lumens & Efficacy	2700K = 41lm 2700K = 50 lm/W		3000K = 43lm 3000K = 51 lm/W		2700K = 41lm 2700K = 50 lm/W		3000K = 43 lm 3000K = 51 lm/W								
Wiring	Wire connection must be made inside fixture				Wire connection must be made inside fixture										
Notes	Included stainless steel mounting hardware and junction box. Designed to be integrated into outdoor steps. Copper and Brass will naturally patina over time. Incandescent version of fixture <b>15070</b> on page 163.				Included stainless steel mounting hardware and junction box. Designed to be integrated into outdoor steps. Incandescent version of fixture <b>15070</b> on page 163.										
Dimensions															
Photometrics															
Mounting Height	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'	
6"	.92	.38	.56	0	0	0	0	1.40	1.20	0.40	0.08	0.03	0.01	0.00	
12"	15	.14	.14	.03	.19	0	0	0.09	0.40	0.29	0.13	0.04	0.02	0.01	